


Safety Data Sheet

SOLID SENSITIVE TAB



Safety Data Sheet dated 20/12/2016, version 2
In compliance with Regulation (EC) 2015/830

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- 1.1. Product identifier
Mixture identification:
Trade name: SOLID SENSITIVE TAB
Product type: Potassium salts-based detergent for self-cleaning ovens
- 1.2. Relevant identified uses of the substance or mixture and uses advised against
Recommended use:
Washing and cleaning products (including solvent based products)
Uses advised against:
Not available
- 1.3. Details of the supplier of the safety data sheet
Supplier:
TURCO ITALIANA SpA, Via Artigianale, 29 - 25010 Montirone (Brescia) - Italy - tel. ++39-030-267443 - fax. ++39-030-2677137 e-mail:info@turco.it
Competent person responsible for the safety data sheet:
info@turco.it
- 1.4. Emergency telephone number
TURCO ITALIANA SpA, - Italy - tel. ++39-030-267443 - fax. ++39-030-2677137
e-mail:info@turco.it (From Monday to Friday from 8:00 to 12:00 and from 13:30 to 17:00)

A list of Poison Control Centers is available at the following link:
http://www.who.int/gho/phe/chemical_safety/poisons_centres/en/

SECTION 2: Hazards identification

- 2.1. Classification of the substance or mixture
EC regulation criteria 1272/2008 (CLP)
- ⚠ Danger, Skin Corr. 1A, Causes severe skin burns and eye damage.
 - ⚠ Danger, Eye Dam. 1, Causes serious eye damage.
 - ⚠ Warning, Skin Sens. 1, May cause an allergic skin reaction.
 - ⚠ Warning, STOT SE 3, May cause respiratory irritation.

EC regulation criteria 1272/2008 (CLP)

Hazard pictograms:



Danger

Hazard statements:

- H314 Causes severe skin burns and eye damage.
- H317 May cause an allergic skin reaction.
- H335 May cause respiratory irritation.

Precautionary statements:

- P280 Wear protective gloves/clothing and eye/face protection.
- P301+P330+P331 IF SWALLOWED: rinse mouth. Do NOT induce vomiting.
- P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.
- P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P310 Immediately call a POISON CENTER or doctor.
- P312 Call a POISON CENTER or physician if you feel unwell.
- P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

Special Provisions:

None

Contains

disodium metasilicate

Safety Data Sheet

SOLID SENSITIVE TAB

Potassium carbonate
Sodium hydroxide
1,2-benzisothiazol-3(2H)-one

Special provisions according to Annex XVII of REACH and subsequent amendments:
None

Declaration of ingredients according to Detergent Regulation 648/2004:
phosphates 15 - 30 %

The product also contains: Disinfectants

2.3. Other hazards

vPvB Substances: None - PBT Substances: None

Other Hazards:

No other hazards

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Hazardous components within the meaning of the CLP regulation and related classification:

10-20 % Sodium hydroxide

REACH N°: 01-2119457892-27-XXXX, Index number: 011-002-00-6, CAS: 1310-73-2,
EC: 215-185-5

◇ 3.2/1A Skin Corr. 1A H314

10-20 % disodium metasilicate

REACH N°: 01-2119449811-37-XXXX, Index number: 014-010-00-8, CAS: 6834-92-0,
EC: 229-912-9

◇ 2.16/1 Met. Corr. 1 H290

◇ 3.2/1B Skin Corr. 1B H314

◇ 3.8/3 STOT SE 3 H335

10-20 % Potassium carbonate

REACH N°: 01-2119532646-36-XXXX, CAS: 584-08-7, EC: 209-529-3

◇ 3.2/2 Skin Irrit. 2 H315

◇ 3.3/2 Eye Irrit. 2 H319

◇ 3.8/3 STOT SE 3 H335

<0.1% 1,2-benzisothiazol-3(2H)-one

Index number: 613-088-00-6, CAS: 2634-33-5, EC: 220-120-9

◇ 3.2/2 Skin Irrit. 2 H315

◇ 3.3/1 Eye Dam. 1 H318

◇ 3.4.2/1-1A-1B Skin Sens. 1,1A,1B H317

◇ 4.1/A1 Aquatic Acute 1 H400 M=1.

◇ 3.1/4/Oral Acute Tox. 4 H302

For the complete text of the hazard and risk phrases refer to paragraph 16

SECTION 4: First aid measures

4.1. Description of first aid measures

In case of skin contact:

Immediately take off all contaminated clothing.

OBTAIN IMMEDIATE MEDICAL ATTENTION.

Remove contaminated clothing immediately and dispose off safely.

After contact with skin, wash immediately with soap and plenty of water.

In case of eyes contact:

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

Protect uninjured eye.

Safety Data Sheet

SOLID SENSITIVE TAB

In case of Ingestion:

Do NOT induce vomiting.

In case of Inhalation:

In case of inhalation, consult a doctor immediately and show him packing or label.

4.2. Most important symptoms and effects, both acute and delayed

None

4.3. Indication of any immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Treatment:

None

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

Water.

Carbon dioxide (CO₂).

Extinguishing media which must not be used for safety reasons:

None in particular.

5.2. Special hazards arising from the substance or mixture

Do not inhale explosion and combustion gases.

Burning produces heavy smoke.

5.3. Advice for firefighters

Use suitable breathing apparatus .

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

Provide adequate ventilation.

Use appropriate respiratory protection.

See protective measures under point 7 and 8.

6.2. Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

Retain contaminated washing water and dispose it.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

Suitable material for taking up: absorbing material, organic, sand

6.3. Methods and material for containment and cleaning up

Wash with plenty of water.

6.4. Reference to other sections

See also section 8 and 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.

Use localized ventilation system.

Don't use empty container before they have been cleaned.

Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.

Contaminated clothing should be changed before entering eating areas.

Do not eat or drink while working.

See also section 8 for recommended protective equipment.

7.2. Conditions for safe storage, including any incompatibilities

Keep away from food, drink and feed.

Incompatible materials:

Safety Data Sheet

SOLID SENSITIVE TAB

None in particular.

Instructions as regards storage premises:

Adequately ventilated premises.

7.3. Specific end use(s)

For more information see Technical data bulletin

None in particular

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Contained substances

Sodium hydroxide - CAS: 1310-73-2

ACGIH - TWA mg/m³(8h): 2 - STEL mg/m³(15min): Ceiling 1.22 - Behaviour:

Binding - Notes: Ingestion: burns to mouth and esophagus, perforation of the gastrointestinal tract. Necrotic tissue. - Les effets critiques: Ceiling irritation of the upper respiratory tract, eye and skin

disodium metasilicate - CAS: 6834-92-0

ACGIH - TWA mg/m³(8h): 10 - Behaviour: Binding - Notes: respirable fraction.

ACGIH - TWA mg/m³(8h): 3 - Behaviour: Binding - Notes: alveolar fraction

DNEL Exposure Limit Values

Sodium hydroxide - CAS: 1310-73-2

Worker Professional: 1 mg/m³ - Consumer: 1 - U.M.: mg/m³ - Exposure: Human

Inhalation - Frequency: Long Term, local effects

disodium metasilicate - CAS: 6834-92-0

Consumer: 0.74 - U.M.: mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects

Worker Professional: 6.22 mg/m³ - Consumer: 1.55 - U.M.: mg/m³ - Exposure:

Human Inhalation - Frequency: Long Term, systemic effects

Worker Professional: 1.49 mg/kg - Consumer: 0.74 - U.M.: mg/kg - Exposure:

Human Dermal - Frequency: Long Term, systemic effects

Potassium carbonate - CAS: 584-08-7

Worker Professional: 16 mg/m³ - Consumer: 8 - U.M.: mg/m³ - Exposure: Human

Dermal - Frequency: Long Term, local effects

Worker Professional: 10 mg/m³ - Consumer: 10 - U.M.: mg/m³ - Exposure: Human

Inhalation - Frequency: Long Term, local effects

PNEC Exposure Limit Values

disodium metasilicate - CAS: 6834-92-0

Target: Marine water - Value: 1 mg/l

Target: Fresh Water - Value: 7.5 mg/l

Target: Occasional issue - Value: 1000 mg/l

Target: Sewerage treatment plants - Value: 7.5 mg/l

8.2. Exposure controls

Eye protection:

Use close fitting safety goggles, don't use eye lens.

Protection for skin:

Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton.

Protection for hands:

Use protective gloves that provides comprehensive protection, e.g. P.V.C., neoprene or rubber.

Respiratory protection:

Use respiratory protection where ventilation is insufficient or exposure is prolonged.

Thermal Hazards:

None

Environmental exposure controls:

None

Appropriate engineering controls:

None

Safety Data Sheet

SOLID SENSITIVE TAB

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Properties	Value	Method:	Notes:
Appearance and colour:	White powder tablets	--	--
Odour:	Odorless	--	--
Odour threshold:	n.av. mg/m ³	--	--
pH:	13	--	--
Melting point / freezing point:	n.av. °C	--	--
Initial boiling point and boiling range:	na °C	--	--
Flash point:	>60 °C	--	--
Evaporation rate:	na	--	--
Solid/gas flammability:	n.av.	--	--
Upper/lower flammability or explosive limits:	na % v/v	--	--
Vapour pressure:	n.av. kPa	--	--
Vapour density (air=1):	> 1	--	--
Relative density:	0.9 g/ml	--	--
Solubility in water:	Complete	--	--
Solubility in oil:	na	--	--
Partition coefficient (n-octanol/water):	na	--	--
Auto-ignition temperature:	na °C	--	--
Decomposition temperature:	na °C	--	--
Viscosity:	n.av. mPa.s	--	--
Explosive properties:	Not explosive	--	--
Oxidizing properties:	Not Oxidant	--	--

9.2. Other information

Safety Data Sheet
SOLID SENSITIVE TAB

Properties	Value	Method:	Notes:
Miscibility:	Complete in water	--	--
Fat Solubility:	na	--	--
Conductivity:	na	--	--
Substance Groups relevant properties:	n.av.	--	--

SECTION 10: Stability and reactivity

- 10.1. Reactivity
Stable under normal conditions
- 10.2. Chemical stability
Stable under normal conditions
- 10.3. Possibility of hazardous reactions
It may generate flammable gases on contact with halogenated organic substances, and elementary metals.
- 10.4. Conditions to avoid
Stable under normal conditions.
- 10.5. Incompatible materials
None in particular.
- 10.6. Hazardous decomposition products
None.

SECTION 11: Toxicological information

- 11.1. Information on toxicological effects
Toxicological information of the product:
Not applicable
- Toxicological information of the main substances found in the product:
Sodium hydroxide - CAS: 1310-73-2
Type: a) acute toxicity:
Test: LD50 - Route: Oral - Species: Rat - Op.: = - Value: 2000 - U.M.: mg/kg
Test: LC50 - Route: Inhalation - Species: Mouse - Op.: = - Value: 4800 - U.M.: mg/l - Duration: 1 hour
Test: LD50 - Route: Skin - Species: Rabbit - Op.: = - Value: 1350 - U.M.: mg/kg
Test: LCLo - Route: Oral - Species: Rabbit - Op.: = - Value: 500 - U.M.: mg/kg
Type: b) skin corrosion/irritation:
Test: Skin Corrosive - Route: Skin - Op.: Positive - Source: OECD 435 - Notes: Studio in vitro
Test: Eye Corrosive - Route: Skin - Species: Rabbit - Op.: Positive - Notes: irreversible effects
Type: h) STOT-single exposure:
Test: Skin Corrosive - Op.: Positive
Test: Respiratory Tract Corrosive - Op.: Positive
disodium metasilicate - CAS: 6834-92-0
Type: a) acute toxicity:
Test: LD50 - Route: Oral - Species: Rat - Op.: > - Value: 1153 - U.M.: mg/kg
Test: LD50 - Route: Oral - Species: Rat - Op.: < - Value: 1349 - U.M.: mg/kg
Test: LC50 - Route: Inhalation - Species: Rat - Op.: > - Value: 2.06 - U.M.: mg/l
Test: LD50 - Route: Skin - Species: Rat - Op.: > - Value: 5000 - U.M.: mg/kg - Duration: 4 hours
Test: NOAEL - Route: Oral - Species: Rat - Op.: = - Value: 227 - U.M.: mg/kg
Test: NOAEL - Route: Oral - Species: Mouse - Op.: = - Value: 260 - U.M.: mg/kg
Type: b) skin corrosion/irritation:
Test: Skin Corrosive - Route: Skin - Species: Rat - Op.: Positive

Safety Data Sheet

SOLID SENSITIVE TAB

Type: c) serious eye damage/irritation:

Test: Eye Corrosive - Route: EYES - Species: Rabbit - Op.: Positive

Potassium carbonate - CAS: 584-08-7

Type: a) acute toxicity:

Test: LC50 - Route: Inhalation - Species: Rat - Op.: > - Value: 4.96 - U.M.: mg/l - Duration: 4.5 hours

Test: LD50 - Route: Oral - Species: Rat - Op.: > - Value: 2000 - U.M.: mg/kg

Test: LD50 - Route: Skin - Species: Rabbit - Op.: > - Value: 2000 - U.M.: mg/kg

1,2-benzisothiazol-3(2H)-one - CAS: 2634-33-5

Type: a) acute toxicity:

Test: LD50 - Route: Oral - Op.: = - Value: 1221 - U.M.: mg/kg

Test: LD50 - Route: Ingestion - Species: Rat - Op.: > - Value: 1150 - U.M.: mg/kg

Test: LD50 - Route: Skin - Species: Rat - Op.: > - Value: 2000 - U.M.: mg/kg

Type: b) skin corrosion/irritation:

Test: Skin Irritant - Route: Skin - Species: Rabbit - Op.: Positive

Type: c) serious eye damage/irritation:

Test: Eye Corrosive - Route: EYES - Species: Rabbit - Op.: Positive

Type: d) respiratory or skin sensitisation:

Test: Skin Sensitization - Route: Skin - Op.: Positive

If not differently specified, the information required in Regulation (EU)2015/830 listed below must be considered as N.A.:

- a) acute toxicity;
- b) skin corrosion/irritation;
- c) serious eye damage/irritation;
- d) respiratory or skin sensitisation;
- e) germ cell mutagenicity;
- f) carcinogenicity;
- g) reproductive toxicity;
- h) STOT-single exposure;
- i) STOT-repeated exposure;
- j) aspiration hazard.

SECTION 12: Ecological information

12.1. Toxicity

Based on the information available it is not expected that this product may cause any adverse environmental effect when use instructions and disposal recommendations are followed.

Adopt good working practices, so that the product is not released into the environment.

List of substances hazardous to the environment and eco-toxicological information available:

Sodium hydroxide - CAS: 1310-73-2

Type: a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish - Op.: > - Value: 35 - U.M.: mg/l - Duration h: 96

Endpoint: LC50 - Species: Fish - Op.: < - Value: 189 - U.M.: mg/l - Duration h: 96

Endpoint: LC50 - Species: Fish - Op.: = - Value: 125 - U.M.: mg/l - Duration h: 96 -

Notes: Gambusia affinis

Endpoint: EC50 - Species: Daphnia - Op.: > - Value: 30 - U.M.: mg/l - Duration h: 48

Endpoint: EC50 - Species: Daphnia - Op.: < - Value: 1000 - U.M.: mg/l - Duration h: 48

Endpoint: EC50 - Species: Daphnia - Op.: = - Value: 40.4 - U.M.: mg/l - Duration h: 48 - Notes: Ceriodaphnia dubia

Type: b) Aquatic chronic toxicity:

Endpoint: NOEC - Species: Fish - Op.: = - Value: 56 - U.M.: mg/l - Duration h: 96 -

Notes: Poecilia reticulata

disodium metasilicate - CAS: 6834-92-0

Type: a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish - Op.: = - Value: 210 - U.M.: mg/l - Duration h: 96 -

Notes: Brachydanio rerio

Safety Data Sheet

SOLID SENSITIVE TAB

Endpoint: LC50 - Species: Fish - Op.: = - Value: 2320 - U.M.: mg/l - Duration h: 96 -
Notes: Gambusia affinis

Endpoint: EC50 - Species: Daphnia - Op.: = - Value: 1700 - U.M.: mg/l - Duration h:
48 - Notes: Daphnia magna

Endpoint: EC50 - Species: Algae - Op.: = - Value: 207 - U.M.: mg/l - Duration h: 72
- Notes: Scenedesmus subspicatus

Potassium carbonate - CAS: 584-08-7

Type: a) Aquatic acute toxicity:

Endpoint: EC50 - Species: Daphnia - Op.: = - Value: 200 - U.M.: mg/l - Duration h:
48 - Notes: Daphnia pulex

Endpoint: LC50 - Species: Fish - Op.: = - Value: 68 - U.M.: mg/l - Duration h: 96 -
Notes: Oncorhynchus mykiss

1,2-benzisothiazol-3(2H)-one - CAS: 2634-33-5

Type: a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish - Op.: = - Value: 2.18 - U.M.: mg/l - Duration h: 96 -
Notes: Onchorhynchus mykiss

Endpoint: LC50 - Species: Fish - Op.: = - Value: 0.16 - U.M.: mg/l - Duration h: 96 -
Notes: Lepomis macrochirus

Endpoint: EC50 - Species: Daphnia - Op.: = - Value: 0.42 - U.M.: mg/l - Duration h:
48 - Notes: Daphnia magna

Endpoint: EC50 - Species: Algae - Op.: = - Value: 0.11 - U.M.: mg/l - Duration h: 72
- Notes: Pseudokirchneriella subcapitata

Endpoint: IC50 - Species: Algae - Op.: = - Value: 0.084 - U.M.: mg/l - Duration h: 72
- Notes: Senedemus subspicatus

Endpoint: EC50 - Species: Bacteria - Op.: = - Value: 30.2 - U.M.: mg/l

Type: b) Aquatic chronic toxicity:

Endpoint: NOEC - Species: Daphnia - Op.: = - Value: 0.0016 - U.M.: mg/l - Notes:
Daphnia magna

12.2. Persistence and degradability

disodium metasilicate - CAS: 6834-92-0

Biodegradability: Readily biodegradable - Test: Not applicable - Duration: Not applicable -
%: Not applicable - Notes: Not applicable

1,2-benzisothiazol-3(2H)-one - CAS: 2634-33-5

Biodegradability: Readily biodegradable - Test: Not applicable - Duration: Not applicable -
%: Not applicable - Notes: Not applicable

Regulation (EC) No. 648/2004 on Detergents and amendments:

Surfactant(s) contained in this preparation comply with biodegradability criteria as defined
in (EC) regulations on detergents.

12.3. Bioaccumulative potential

Sodium hydroxide - CAS: 1310-73-2

Bioaccumulation: Not bioaccumulative - Test: Not applicable Not applicable - Duration:
Not applicable - Notes: Not applicable

disodium metasilicate - CAS: 6834-92-0

Bioaccumulation: Not bioaccumulative - Test: Not applicable Not applicable - Duration:
Not applicable - Notes: Not applicable

1,2-benzisothiazol-3(2H)-one - CAS: 2634-33-5

Bioaccumulation: Not bioaccumulative - Test: BCF - Bioconcentration factor 6.95 -
Duration: Not applicable - Notes: Not applicable

12.4. Mobility in soil

Sodium hydroxide - CAS: 1310-73-2

Mobility in soil: Mobile - Test: Not applicable Not applicable - Duration: Not applicable -
Notes: Not applicable

12.5. Results of PBT and vPvB assessment

vPvB Substances: None - PBT Substances: None

12.6. Other adverse effects

None

SECTION 13: Disposal considerations

1SOLIDSSENSITAB/2

Page n. 8 of 12

Safety Data Sheet

SOLID SENSITIVE TAB

13.1. Waste treatment methods

Product and its residue:

Do not dispose in the canals of wastewater, waterways and soil.

The codes indicating the type of waste are considered based on the recommendations and scheduled use of this product. Different codes may be assigned based on the end user's use and the characteristics of the disposal.

Waste code CER/EWC (2000/532/CE), attributable to the product as:

06 02 04 * Sodium and potassium hydroxide

HP8 - HP5

Any remaining product should be disposed of with the material.

Containers/contaminated packaging

Containers, even completely empty, must not be disposed in the environment. The packagings which can not be cleaned should be disposed of as the material.

Recover, if possible. Send to authorised disposal plants or for incineration under controlled conditions. In so doing, comply with the local and national regulations currently in force.

SECTION 14: Transport information



14.1. UN number

ADR-UN Number: 3262

IATA-UN Number: 3262

IMDG-UN Number: 3262

14.2. UN proper shipping name

ADR-Shipping Name: CORROSIVE SOLID, BASIC, INORGANIC, N.O.S.(Disodium metasilicate, Sodium hydroxide)

IATA-Shipping Name: CORROSIVE SOLID, BASIC, INORGANIC, N.O.S.(Disodium metasilicate, Sodium hydroxide)

IMDG-Shipping Name: CORROSIVE SOLID, BASIC, INORGANIC, N.O.S.(Disodium metasilicate, Sodium hydroxide)

14.3. Transport hazard class(es)

ADR-Class: 8

ADR - Hazard identification number: 80

IATA-Class: 8

IATA-Label: 8

IMDG-Class: 8

14.4. Packing group

ADR-Packing Group: II

IATA-Packing group: II

IMDG-Packing group: II

14.5. Environmental hazards

ADR-Environmental Pollutant: No

IMDG-Marine pollutant: No

14.6. Special precautions for user

ADR-Subsidiary risks: -

ADR-S.P.: 274

ADR-Transport category (Tunnel restriction code): (E)

IATA-Passenger Aircraft: 859

IATA-Subsidiary risks: -

IATA-Cargo Aircraft: 863

IATA-S.P.: A3 A803

IATA-ERG: 8L

IMDG-EmS: F-A , S-B

IMDG-Subsidiary risks: -

Safety Data Sheet

SOLID SENSITIVE TAB

IMDG-Stowage and handling: Category B
IMDG-Segregation: SG35
14.7. Transport in bulk according to Annex II of Marpol and the IBC Code
No

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture
Dir. 98/24/EC (Risks related to chemical agents at work)
Dir. 2000/39/EC (Occupational exposure limit values)
Regulation (EC) n. 1907/2006 (REACH)
Regulation (EC) n. 1272/2008 (CLP)
Regulation (EC) n. 790/2009 (ATP 1 CLP) and (EU) n. 758/2013
Regulation (EU) 2015/830
Regulation (EU) n. 286/2011 (ATP 2 CLP)
Regulation (EU) n. 618/2012 (ATP 3 CLP)
Regulation (EU) n. 487/2013 (ATP 4 CLP)
Regulation (EU) n. 944/2013 (ATP 5 CLP)
Regulation (EU) n. 605/2014 (ATP 6 CLP)
Regulation (EU) n. 2015/1221 (ATP 7 CLP)

Restrictions related to the product or the substances contained according to Annex XVII Regulation (EC) 1907/2006 (REACH) and subsequent modifications:

Restrictions related to the product:

No restriction.

Restrictions related to the substances contained:

No restriction.

Volatile Organic compounds - VOCs = 0.00 %

Volatile Organic compounds - VOCs = 0.00 g/l

Volatile CMR substances = 0.00 %

Halogenated VOCs which are assigned the risk phrase R40 = 0.00 %

Organic Carbon - C = 0.00

Where applicable, refer to the following regulatory provisions :

Regulation (EC) n°648/2004 (detergents).

Dir. 2004/42/EC (VOC directive)

Seveso III category according to Annex 1, part 1

Product belongs to category: Not applicable

15.2. Chemical safety assessment

No Chemical Safety Assessment has been carried out for the mixture.

SECTION 16: Other information

Full text of phrases referred to in Section 3:

H314 Causes severe skin burns and eye damage.

H290 May be corrosive to metals.

H335 May cause respiratory irritation.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H318 Causes serious eye damage.

H317 May cause an allergic skin reaction.

H400 Very toxic to aquatic life.

H302 Harmful if swallowed.

Hazard class and hazard category	Code	Description
Met. Corr. 1	2.16/1	Substance or mixture corrosive to metals, Category 1

Safety Data Sheet

SOLID SENSITIVE TAB

Acute Tox. 4	3.1/4/Oral	Acute toxicity (oral), Category 4
Skin Corr. 1A	3.2/1A	Skin corrosion, Category 1A
Skin Corr. 1B	3.2/1B	Skin corrosion, Category 1B
Skin Irrit. 2	3.2/2	Skin irritation, Category 2
Eye Dam. 1	3.3/1	Serious eye damage, Category 1
Eye Irrit. 2	3.3/2	Eye irritation, Category 2
Skin Sens. 1	3.4.2/1	Skin Sensitisation, Category 1
Skin Sens. 1,1A,1B	3.4.2/1-1A-1B	Skin Sensitisation, Category 1,1A,1B
STOT SE 3	3.8/3	Specific target organ toxicity - single exposure, Category 3
Aquatic Acute 1	4.1/A1	Acute aquatic hazard, category 1

Paragraphs modified from the previous revision:

SECTION 2: Hazards identification
 SECTION 3: Composition/information on ingredients
 SECTION 8: Exposure controls/personal protection
 SECTION 9: Physical and chemical properties
 SECTION 11: Toxicological information
 SECTION 12: Ecological information
 SECTION 15: Regulatory information

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Classification according to Regulation (EC) Nr. 1272/2008	Classification procedure
Skin Corr. 1A, H314	On basis of test data (pH)
Eye Dam. 1, H318	On basis of test data (pH)
Skin Sens. 1, H317	Calculation method
STOT SE 3, H335	Calculation method

This document was prepared by a competent person who has received appropriate training.
 This MSDS cancels and replaces any preceding release.

Where applicable, refer to the following regulatory provisions :

Council Directive 67/548/EEC (Classification, packaging and labelling of dangerous substances) and subsequent amendments; Regulation (EC) n°1272/2 008; Regulation (EC) N. 790/2009 (annex VI), Regulation (EC) n. 1907/2006 (REACH).

Commission Directive 1999/45/EC (Classification, packaging and labelling of dangerous preparation) and subsequent amendments; Commission Directive n. 2006/8/CE.

Directive 2012/18/EU (Seveso III)

Directive 2013/10/EU (aerosols) amending Directive 75/324/EEC on the approximation of the laws of the Member States relating to aerosol dispensers in order to adapt its labelling

Safety Data Sheet

SOLID SENSITIVE TAB

provisions to Regulation (EC) n° 1272/2008 on classification, labelling and packaging of substances and mixtures and subsequent amendments.

Regulation (EC) No 1223/2009 on cosmetic products and subsequent amendments.

Regulation (EU) No 126/2013 amending Annex XVII to Regulation (EC) No 1907/2006 on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) and subsequent amendments. Regulation (EC) N. 304/2003 and subsequent amendments. Regulation (EU) No 528/2012 concerning the making available on the market and use of biocidal products and subsequent amendments.

EU Regulation 1357/2014 (Disposal of waste) and subsequent amendments.

The European Agreement concerning the International Carriage of Dangerous Goods by Road (ADR), current edition.

Regulations IATA/ICAO = Dangerous Goods Regulations by air, current edition.

RID = Regulations concerning the International Carriage of Dangerous Goods by Rail, current edition.

IMDG Code = International Maritime Dangerous Goods Code produced by the International Maritime Organization (IMO), current edition.

Main bibliographic sources:

ESIS: European chemical Substances Information System and Environmental hazard classification.

Occupational exposure limit values (Commission Directives 2000/39/EC and 2006/15/CE)

NIOSH - Registry of toxic effects of chemical substances (1983)

Material Safety Data Sheets of chemicals, REACH database

Material Safety Data Sheet and Technical Data of raw material as by Supplier.

Abbreviations and acronyms:

TLV-TWA = Threshold Limit Value- time-weighted average, 8-hour workday, 40-hour workweek;

TLV-STEL-15 min = Threshold Limit Values - Short Term Exposure Limit; TLV-C = Ceiling

exposure limit; Notes: IBE= Biological Exposure Indices; SEN= sensitizer; Skin= Can be absorbed through the skin. Carcinogenicity categories: A1 / A2 = confirmed / suspected human carcinogen; A3 = Animal carcinogen; A4 / A5 = Not Classifiable/not suspected as a human carcinogen. ACGIH = American Conference on Governmental Industrial Hygienists. OEL =Occupational Exposure Limit. VLPE = Occupational Exposure Limit Values. LTE =long term exposure, STE=short term exposure.

n.av.= Not Available, n.a. = not applicable; LD50=lethal dose (solids and liquids), LC50=lethal concentration (gases) that will kill 50% of the test animals; ADR= European Agreement concerning the International Carriage of Dangerous Goods by Road. Regulations IATA/ICAO = Dangerous Goods Regulations by air, current edition.

RID = Regulations concerning the International Carriage of Dangerous Goods by Rail, current edition. IMDG Code = International Maritime Dangerous Goods Code produced by the International Maritime Organization (IMO), current edition.

PBT = Persistent, Bioaccumulative and Toxic substances. ; vPvB = very Persistent and very Bioaccumulative substances; CMR = Carcinogenic, mutagenic or reproduction toxic substances.

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.